AD-A264 028

(2)

OFFICE OF NAVAL RESEARCH CONTRACT N00014-91-J-1590 R & T Project Code 4132053

TECHNICAL REPORT NO. 41



APPLICATIONS OF TRANSITION METAL COMPOUNDS IN THE PREPARATION OF USEFUL SILICON-CONTAINING CERAMICS

by

Dietmar Seyferth

To Be Published in

Münchner Silicontage (VCH Publishers)

Department of Chemistry

Massachusetts Institute of Technology

Cambridge, MA 02139

April 20, 1993

93-10099

Reproduction in whole or in part is permitted for any purpose of the United States Government

This document has been approved for public release and sale; its distribution is unlimited

93 5 07 050

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public requiring durage for this collection of information is estimated to aversale. Incur per response including the sime for reviewing instructions, searthing existing daria sources game, as many the data needed and completing and reviewing the otterior of other formation. Send comments regarding this burden estimate or any other acceptances and formation of collections for information of collections for reducing this ourden to washing on treadquarters services. Discription of collections and Reports 1975 Letters on Dassington, visit 1222-302, and to the Office of the requestion of project (0.704,0.168) washington, visit 1222-302, and to the Office of the requestion of the other project (0.7050).

1. AGENCY USE ONLY (Leave of	1993-4-20	J REPORT TYPE AN	ND DATES COVERED
4. TITLE AND SUBTITLE Applications of Tr Preparation of Use 6. AUTHOR(5) Dietmar Seyferth	ransition Metal Compo eful Silicon-Containi	unds in the ng Ceramics	5. FUNDING NUMBERS N=00014-91-J1590
7. PERFORMING ORGANIZATION Massachusetts Instite Department of Chemite 177 Massachusetts Avandaridge, MA 0213 9. SPONSORING/MONITORING AVANDED 18 Department of the National Research 18 Office of Naval Research 18 One North Quincy Starlington, VA 2221 11. SUPPLEMENTARY NOTES to be published in	tute of Technology stry enue 9 GENCY NAME(S) AND ADDRESS(avy earch reet		8. PERFORMING ORGANIZATION REPORT NUMBER 41 10. SPONSORING/MONITORING AGENCY REPORT NUMBER 4132038
purpose of the Uni	ole or in part is pe ted States governmen for public release a	t. This document	12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 wor A brief review of as applied to Si-H	ds) transition metal comp containing polysilan	olex catalyzed cro	esslinking chemistry
14. SUBJECT TERMS			15. NUMBER OF PAGES
17. SECURITY CLASSIFICATION	18. SECURITY CLASSIFICATION	19. SECURITY CLASSIFIC	16. PRICE CODE
OF REPORT unclassified	OF THIS PAGE unclassified	OF ABSTRACT unclassified	unlimited

Applications of Transition Metal Compounds in the Preparation of Useful Silicon-Containing Ceramics

Dietmar Seyferth

Department of Chemistry
Massachusetts Institute of Technology
Cambridge, MA 02139 USA

There have been many studies of the reactions of organosilicon compounds with diverse transition metal complexes [1]. The original impetus for this research activity was given by the discoveries that heterogeneous platinum and palladium catalysts [2,3] and chloroplatinic acid [3] were effective hydrosilylation catalysts. In the years that followed, many other transition metal complexes have been found to catalyze the addition of silicon hydrides to organic multiple bonds. Also, transition metal complexes have been found to catalyze other reactions of organosilicon compounds, such as the insertion of acetylenes and other unsaturated organic compounds into reactive Si-Si bonds [5] and reactions of the Si-C bonds of strained cyclic organosilicon compounds [6]. A different focus on silicontransition metal chemistry was found in Aylett's preparation of H₃Si-transition metal compounds [7]. These were found to be effective precursors for transition metal silicides by chemical vapor deposition. This potentially useful application in materials processing led to further work by others on the synthesis of transition metal complexes containing metal-silicon bonds.

More recently, it was the seminal work of Aitken, Harrod and Samuel which showed that Group IV metallocene compounds catalyzed the dehydrogenative coupling of primary silanes, RSiH₃, to give polysilanes of relatively low molecular weight, [RSiH]_n [8], that attracted many others into the silicon/transition metal chemistry field [9].

In our research at MIT we have found transition metal chemistry a very useful aid in

the preparation of silicon-containing ceramics by the polymer pyrolysis procedure.

By
Distribution /
Availability Codes
Dist | Avail and for |
Special

i or

CRASI

TAB

DTIC Question of the control of 3

One of the silicon-containing preceramic polymers that we prepared is poly(methylsilane). It was discovered by T.G. Wood in our laboratories [10] and, independently, by Brown-Wensley and Sinclair at the 3M Company [11], that the the action of an excess of metallic sodium on methyldichlorosilane, CH3SiHCl2, results in complete dechlorination and usually partial dehydrogenation to give polysilanes of type [(CH3SiH)x(CH3Si)y-(CH₃SiH₂)_z]_n. The CH₃SiH₂ end groups are detectable by ²⁹Si NMR (DEPT). For simplicity's sake, we write the polysilane as $[(CH_3SiH)_x(CH_3Si)_y]_n$, where x + y = 1 and x and y are derived from the integrated ¹H NMR spectrum. The CH₃SiH₂ end groups could result from a disproportionation reaction, but their provenance in unknown at this time. When the CH₃SiHCl₂/Na reaction is carried out in 7: 1 (v/v) hexane/tetrahydrofuran (THF), very little Si-H functionality is lost and $x \sim 0.75 - 0.98$. When, on the other hand, the reaction is carried out in THF alone, there is substantial loss of Si-H functionality and $x \sim 0.4$. Those poly(methylsilanes) where $x \sim 0.75 - 0.98$ are liquids of relatively low molecular weight (n ~ 14-16). Since their extent of crosslinking is very low, the ceramic residue yield obtained in their pyrolysis in argon is low (15 - 25%). A substantial fraction of the methyl groups is lost as CH4 in the pyrolysis. As a result, the pyrolysis residue contains around 24% by weight of elemental silicon as well as the expected β -SiC. The poly(methylsilane) that is produced in the reaction carried out in THF is a soluble solid and is more highly crosslinked. Consequently, its pyrolysis gives a 60% ceramic residue yield. However, here also methyl group loss is substantial and the ceramic residue again contains about 25% elemental silicon.

These problems, low ceramic yield and formation of substantial amounts of elemental silicon in the pyrolysis, can be dealt with in a number of ways. Transition metal-catalyzed cross-linking has been found to be particularly effective [12].

In view of Harrod's findings that $(\eta^5-C_5H_5)_2M(CH_3)_2$ (M = Ti, Zr) compounds are effective catalysts for the dehydrogenative coupling of mono- and diorganosilanes, we studied the action of these and related complexes on the liquid poly(methylsilane) obtained by sodium condensation of CH_3SiHCl_2 . The compounds $[(\eta^5-C_5H_5)_2ZrH_2]_n$,

 $(\eta^5-C_5H_5)_2$ ZrHCl, $(\eta^5-C_5H_5)_2$ Zr(CH₃)₂ and $(\eta^5-C_5H_5)_2$ Ti(CH₃)₂ were found to be effective catalysts for the crosslinking of poly(methylsilane). Products that were still soluble but that on pyrolysis gave ceramic residue yields in the range 70-85% were obtained. The catalysts, used in 0.5 - 1.5 mol % quantity, could be activated by UV irradiation (methyl compounds only) or thermally. An added, unexpected benefit of using these catalysts was that the pyrolysis residue was near-stoichiometric silicon carbide. Thus in the case of the $[(\eta^5-C_5H_5)_2ZrH_2]_n$ catalyst, the residue, by elemental analysis, had the nominal composition, by weight, 98% SiC, 1.6% ZrC and 0.4% Si. X-ray powder diffraction of the residue showed lines due to β -SiC and none due to elemental silicon. Integration of the proton NMR spectra of the poly(methylsilane) before and after treatment with the organozirconium or -titanium catalyst showed that there had been a significant loss of Si-H functionality. Thus dehydrogenative coupling very likely had taken place. The ²⁹Si NMR spectrum of the crosslinked poly(methylsilane) showed that the CH₃SiH₂ moieties (which could be expected to be more reactive than the internal CH₃SiH groups) had almost disappeared. The catalyst residues, being nonvolatile, remained in the polymer and thus some small amounts of TiC or ZrC ended up in the ceramic obtained on pyrolysis of the crosslinked poly(methylsilane). At this time it is not known whether or not the transition metal moieties are chemically bound to the poly(methylsilane).

In view of current interest in composites containing two or more ceramics, e.g., SiC/TiC [13], we have extended this work to include stoichiometric reactions of the liquid poly(methylsilane) with $(\eta^5-C_5H_5)_2M(CH_3)_2$ (M = Ti, Zr, Hf) compounds [14]. The UV irradiation of mixtures of these reactants in hexane under argon resulted in formation of THF- and toluene-soluble brown to black, air-sensitive solids that still contained η^5 -cyclopentadienyl groups. Their pyrolysis, in argon to 1500 °C, gave ceramic residues in high yield. X-ray diffraction established the presence of β -SiC as well as of the respective MC and elemental analysis indicated that substantial amounts of free carbon were present. Selected results are given in Table I. The excess free carbon was undesirable and could be dealt with in two ways. In the first, the ceramic product, was heated to ~1000 °C in a

Table I. Ceramics Obtained in the Pyrolysis of the Methylpolysilane/(η⁵-C₅H₅)₂MMe₂ Reaction Product Polymers to 1500° C in a Stream of Argon

		Ceramic	Relative molar amount of phase (% by weight of phase)		
	SiH: Metal Ratio	Yield	MC	SiC	C
M = Ti	1.00 : 1.05	78%	1.00 (28.9%)	1.61 (31.2%)	6.85 (39.9%)
M = Zr	1.00 : 0.49	84%	1.00 (29.3%)	3.69 (42.0%)	8.43 (28.7%)
M = Hf	1.00: 0.32	67%	1.00 (34.8%)	6.24 (45.7%)	8.90 (19.5%)

stream of ammonia. This served to react away the free carbon (as HCN and H₂ [15]) and to convert the ZrC to zirconium nitride. Thus a SiC/ZrN composite had resulted. Alternatively, enough of a metal powder was added to poly(methylsilane)/ (n⁵-C₅H₅)₂M(CH₃)₂ reaction product to react with the expected free carbon at high temperature [14]. Thus when in one experiment an initimate mixture of the poly(methylsilane)/ (η⁵-C₅H₅)₂Ti(CH₃)₂ reaction product and titanium powder was heated to 1500 °C in argon, a ceramic product that X-ray diffraction showed to contain β-SiC and TiC was obtained. Elemental analysis established a nominal composition of 64.5% TiC, 35.0% SiC and 0.5% C (by weight). A ternary composite could be prepared when, for instance, $(\eta^5-C_5H_5)_2Zr(CH_3)_2$ was used and the added metal powder was Ti. The pyrolysis of intimate mixtures of silicon-containing preceramic powders with transition metal powders has been used to generate ceramic phases other than those obtained when the polymer is pyrolyzed alone [16]. Tables II and III give selected results for such pyrolyses of the [(CH₃Si(H)NH)_a(CH₃SiN)_b]_n polysilazane [17] with transition metal powders in argon and in ammonia; Table IV, selected results of the pyrolysis of the Nicalon polycarbosilane with transition metal powders in argon. It is seen that this procedure provides a useful route to MC/SiC composites, to transition metal silicides and, in cases where the metal nitride is very stable, to SiC/MN composites.

Table IL Ceramic Products from Metal Powder-Polysilazane Composites Pyrolyzed to 1500° C Under a Flow of Argon.

Metal	M : Si	C e ramic yield (%)	XRD results
Ti	1.2 : 1	72	TiN + SiC
Zr	1.3:1	82	ZrN + SiC
V	1:1	54	V ₅ Si ₃ + SiC
Nb	1:1	80	NbC + NbSi ₂
Mo	1:2	73	MoSi ₂ + Mo ₅ Si ₃
Mo	1:1	80	Mo ₅ Si ₃
W	1:1	87	$WC + WSi_2 + W_5Si_3 + SiC$
W	5:3	93	WC + W ₅ Si ₃

Table III. Ceramic Products from Metal Powder-Polysilazane Composites Pyrolyzed at 800° C for 4h Under Ammonia Flow, then at 1500° C Under a Flow of Argon.

Metal	M : Si	Ceramic yield (%)	XRD results
V	1:1	49	V ₂ N + V ₅ Si ₃
Mo	1:1	73	Mo ₅ Si ₃
W	1:2	76	$W_5Si_3 + WSi_2$
W	5:3	89	W ₅ Si ₃ *

^{*} Anal.: W, 93.32; Si, 4.42; C, N, <5.

Table IV. Ceramic Products from Metal Powder-Nicalon PCS Composites Pyrolyzed to 1500° C Under a Flow of Argon.

Metal	M : Si	Ceramic yield (%)	XRD results
Mo	1:1	91	α-Mo ₂ C + Mo ₅ Si ₃ + SiC
W	1:2	85	WC + WSi ₂ + SiC *
Ti	1:1	80	TiC + SiC
Zr	1:1	87	ZrC + SiC
V	1:1	79	V ₈ C ₇ + SiC
Nb	1:1	85	NbC + SiC
Ta	1:1	83	TaC + SiC

^{*} Anal.: W, 68.73; Si, 16.77; C, 10.80 (equiv. to ~ 0.38 WC, 0.59 SiC, 0.03 WSi₂)

Other organosilicon polymer precursors for ceramics have either been prepared or improved by means of transition metal complex-catalyzed chemistry. For instance, the Nicalon silicon carbide-based ceramic fibers are fabricated from a polycarbosilane that is produced by thermal rearrangement of poly(dimethylsilylene) [18]. The CH₃(H)SiCH₂ group is the major constituent of this polycarbosilane. Pyrolysis of the uncured Nicalon polycarbosilane typically gives ceramic residue yields of 55-60%. We found that this polymer may be further crosslinked to give soluble products by treatment with small quantities (0.25 - 1.5 mol%) of a metal carbonyl, using either UV irradiation or thermal activation [19]. Co₂(CO)₈, Co₄(CO)₁₂ are particularly effective. This approach was suggested by the known stoichiometric reactions of molecular organosilicon hydrides with transition metal carbonyls to give products containing transition metal-silicon bonds [20]. Pyrolysis of these crosslinked polymers resulted in ceramic residue yields in the 80-90% range.

Polysilazanes that can serve as precursors for silicon carbonitride have been prepared using a Ru₃(CO)₁₂-catalyzed Si-H/N-H dehydrogenative coupling process by workers at SRI [21]. Thus the ammonolysis product of CH₃SiHCl₂, whose composition approximates [CH₃Si(H)NH]_n, could be crosslinked by heating at 40 °C with a catalytic quantity of Ru₃(CO)₁₂. Other polysilazanes were prepared by this procedure:

This brief review has shown that the transition metals and their compounds can play a very useful role in ceramics-directed silicon chemistry. Transition metal complexes find important applications as catalysts as well as stoichiometric reactants, and the metals themselves have found more direct application in the synthesis of silicon-containing ceramics and ceramic composites.

Acknowledgement. I acknowledge, with thanks, the research of my capable coworkers at MIT: T.G. Wood, G.H. Wiseman, H.J. Tracy, C.A. Sobon, J.L. Robison, P.A. Czubarow, N. Bryson, and J. Borm. and the financial support by the Office of Naval Research, the Air Force Office of Scientific Research, and Akzo Corporate Research America, Inc.

REFERENCES

- [1] (a) F. Höfler, Topics Current Chem, 50 (1974) 129.
 - (b) T.D. Tilley, in "The Chemistry of Organic Silicon Compounds", Part 2, edited by S. Patai, Wiley-Interscience: New York, 1989, 1415-1477.
- [2] G.H. Wagner, US patent 2,632,013 (1953); Chem. Abstr., 48 (1954) 2760.
- [3] J.L. Speier, J.A. Webster and G.H. Barnes, J. Am. Chem. Soc., 79, (1957) 974.
- [4] (a) E. Lukevics, Z.V. Belyakova, M.G. Pomerantseva and M.G. Voronkov, J. Organomet. Chem. Library, 5 (1977), 1.
 - (b) I. Ojima and T. Kogure, Rev. Si, Ge, Sn, Pb Cpds, 5 (1981) 7.
- [5] For instance: H. Watanabe, M. Kobayashi, K. Higuchi and Y. Nagai, J. Organomet. Chem., 136 (1980) 51.
- [6] For instance: M. Ishikawa, H. Sugisawa, M. Kumada, T. Higuchi, K. Matsui and K. Hirotsu, *Organometallics*, 1 (1982) 1473.
- [7] B.H. Aylett and H.M. Colquhoun, J. Chem. Soc., Dalton Trans. (1977) 2058.
- [8] C. Aitken, J.F. Harrod and E. Samuel, J. Organomet. Chem., 279 (1985) C11.
- [9] Reviews: (a) J.F. Harrod and Y. Mu, Polyhedron, 10 (1991) 1239.
 - (b) R.M. Laine, in "Aspects of Homogeneous Catalysis", edited by R. Ugo, Kluwer Academic Publishers: the Netherlands, Vol. 7, 1990, p. 37.
 - (c) J.Y. Corey, in "Advances in Silicon Chemistry", Vol. 1, JAI Press: Greenwich, 1991, p. 327.
- [10] T.G. Wood, Ph.D. Dissertation, MIT, 1984.
- [11] K.A. Brown-Wensley and R.A. Sinclair, US patent 4,537,942 (1985).

- [12] D. Seyferth, T.G. Wood, H.J. Tracy and J.L. Robison, J. Am. Ceram. Soc., 75 (1992) 1300.
- [13] H. Endo, M. Ueki and H. Kubo, J. Mater. Sci., 25 (1990) 2503.
- [14] D. Seyferth, H. Lang, C.A. Sobon, J. Corm, H.J. Tracy and N. Bryson, J. Inorg. Organomet. Polym., 2 (1992) 59.
- [15] F.K. van Dijen and J. Pluijmakers, J. Europ. Ceram. Soc., 5 (1989) 385.
- [16] D. Seyferth, N. Bryson, D.P. Workman and C.A. Sobon, J. Am. Ceram. Soc., 74 (1991) 2687.
- [17] D. Seyferth and G.H. Wiseman, J. Am. Ceram. Soc., 67 (1984) C-132; US patent 4,482,669 (1984).
- [18] S. Yajima, Am. Ceram. Soc. Bull., 62 (1983) 893.
- [19] D. Seyferth, C.A. Sobon and J. Borm, New J. Chem., 14 (1990) 545.
- [20] (a) S.A.R. Knox and F.G.A. Stone, J. Chem. Soc. A (1969) 2559; (1970) 3147.
 - (b) A. Brooks, S.A.R. Knox and F.G.A. Stone, J. Chem. Soc. A (1971) 3469.
- [21] (a) Y.D. Blum and R.M. Laine, Organometallics, 5 (1986) 2081.
 - (b) C. Biran, Y.D. Blum, R. Glaser, D.S. Tse, K.A. Youngdahl and R.M. Laine, J. Molec. Catal., 48 (1988) 183.
 - (c) K.A. Youngdahl, R.M. Laine, R.A. Kennish, T.R. Cronin and G.G.A. Balavoine, *Mat. Res. Soc. Symp. Proc.*, 121 (1988) 489.
 - (d) Y.D. Blum, K.B. Schwartz, E.J. Crawford and R.D. Hamlin, Mat. Res. Soc. Symp. Proc., 121 (1988) 565.